



Data Sheet: Sacrificial Anti-Graffiti Coating

Self emulsifiable coating that can be removed simply by using hot, high pressure water taking graffiti and pollutants with it. Invisible once applied it does not change the appearance of masonry. It is permeable to water vapour and dry to the touch.

Benefits

- Does not change the colour of masonry
- Easily removed with hot water
- Permeable to water vapour
- Graffiti and pollutants easily removed
- Silicone and fluoropolymer-free
- Solvent free means low VOC

Specification

Appearance:	Thin, mobile liquid
Colour:	White
S.G:	1.00
Solids:	9.0
Container size:	1 litre and 5 litre

Dilution

Use neat as supplied. No need to dilute.

NB Can dull polished surfaces. Use on vertical surfaces only.

Always apply to test area to check suitability before overall treatment.

Coverage per litre.

Polished surfaces and tiles:	3 to 6 m ²
Un-polished and porous surfaces:	2 to 5 m ²
Brick, concrete, terracotta:	2 to 5 m ²

Application Method

Surface must be clean and dry - slightly damp is OK especially if retreating after removal.

Apply by brush or low pressure spray to saturate the surface. Two coats are usually necessary leaving 3 to 4 hours between coats. Do not apply at below 5C.

Removal

Pressure wash with water at 90°, 80 to 90 bar. Graffiti and soiling will be removed with the coating.

