



Data Sheet: Toolclean

Description

Toolclean is an equipment cleaner suitable for the removal of uncured Epoxy, Polyester and Polyurethane resins. It has a low evaporation rate, mild odour and low toxicity, making it much more user friendly than other commonly used solvents.

Toolclean is also largely biodegradable and photochemically non reactive, and therefore more acceptable from an environmental point of view.

Typical Uses

- Paint and Graffiti removal
- Equipment cleaning.
- Uncured resin removal

Advantages

- Low Hazard
- Low evaporation rate
- Excellent solvency powers
- 80% Biodegradable

Health and Safety

Do not breathe vapour / spray.
Avoid contact with skin and eyes.
Provide adequate ventilation

Refer to Safety Data Sheet for further information.

SDS can be downloaded at www.urbanhygiene.com

Physical Data

Appearance: Clear, colourless liquid

Odour: Mild (or faint). Alcohol

Components 1

Dry film thickness N/A

Number of applications 1 (usually)

Flash Point 31°C

Vapour Pressure 10mm Hg @ 20°C

Specific Gravity 0.921 @ 20°C

Solubility in water Soluble

Application By brush or roller.
Can also be sprayed

Pot life at 20°C Unlimited

Storage life 12 months in cool, dry place in sealed containers

Flammable Yes

Packaging

Toolclean is supplied in 5 litre packs

